

C³ COMPACT CURVE CONVEYOR

Dorner's C³ conveyor system, featuring our signature low-profile frame, introduces a groundbreaking curved belt and drive mechanism.

FEATURES

- Best for bakery & confectionary products, packaging and material handling
- Sprocket driven belt technology provides low tension allowing for minimal belt stretch.
- Seamless transfers of small products with 25 mm pulley
- BISSC-certified and FDA-approved materials

SPECIFICATIONS

- 12kg (26 lbs.) non-accumulating load maximum
- Speeds up to 42 m/min (138 ft./min)
- 45°, 90°, and 180° angles available
- 25 mm pulley
- Inner Radius Widths: 150, 300, 450, and 600 mm.
- Outer Radius Widths: 450, 600, 750, 900 mm.
- Top or bottom Mounts for 90° motors
- Parallel motors come in AC and 24DC versions
- Belting options include FDA high friction white, FDA high friction blue, and FDA low friction blue
- Stand options include table-top with adjustable 3mm shims, short stands with casters or fixed foot with 20-30mm adjustable range, and standard stands with casters or fixed foot with 50-500 mm adjustable range

Options & Accessories


- Guiding Options
 - Product comes with 18mm high side guiding
 - 75 mm or 150 mm high side optional
- Custom options include stainless steel stands and motors
- Standard alignment brackets for transfers to 2200, 2700, and AquaGard LP conveyors

DORNER[®]

By Columbus McKinnon



Seamless Transfers of Small Products



Optional High Side Guiding

TRANSFORMING CONVEYOR AUTOMATION

Dorner – North & South America

www.dornerconveyors.com

USA
(262) 367-7600

Canada
(289) 208-7306

Latin America
+52.33.30037400

Configure today with

UTools

